




# Kirlin Select

INTEGRATED MODULE SERIES

## Kirlin Offers These **Exclusive** Benefits:


- Wet Location, IC Rated Standard
- Shallow 4-3/8" depth
- Rustproof and corrosion free luminaire; exceeds 1,000 hour ASTM 5% salt spray test
- 1% low end dimming, 0-10V
- Color temperature 3500K; optional 3000K, 4100K
- Wide flood; fewer fixtures (1.2 SC)
- 2000, 1500 or 1100 lumen designs
- 80+ CRI
- White trims, optional SofTex™ or custom colors
- Full 5 year warranty
- No remote phosphor (eliminates "egg yolk")
- Ultra high efficacy integrated compact module: lighthead, driver, heatsink

[www.kirlinlighting.com](http://www.kirlinlighting.com)

4"



LRR-04102-2000L  
LRR-04102-1500L  
LRR-04102-1100L



1988 LUMENS

20.3W


WFL

SC: 1.2

LPW: 98

MAXIMUM PERFORMANCE (-2000L SERIES)

Cone of Light ▲




Dist.	FC	Dia.
6	28.3	7.2
8	15.9	9.6
10	10.2	12.0
12	7.1	14.4
14	5.2	16.8
16	4.0	19.2

6"

Downlight



LRR-06103-2000L  
LRR-06103-1500L  
LRR-06103-1100L



1984 LUMENS

19.9W


WFL

SC: 1.2

LPW: 100

MAXIMUM PERFORMANCE (-2000L SERIES)

Cone of Light ▲




Dist.	FC	Dia.
6	27.7	7.3
8	15.6	9.8
10	10.0	12.2
12	6.9	14.7
14	5.1	17.1
16	3.9	19.5

4"



LRR-04105-2000L  
LRR-04105-1500L  
LRR-04105-1100L



1873 LUMENS

20.1W


WFL

SC: 1.2

LPW: 93

MAXIMUM PERFORMANCE (-2000L SERIES)

Cone of Light ▲




Dist.	FC	Dia.
6	28.7	6.9
8	16.1	9.2
10	10.3	11.5
12	7.2	13.9
14	5.3	16.2
16	4.0	18.5

5"

Shower Light



LRR-05110-2000L  
LRR-05110-1500L  
LRR-05110-1100L



1351 LUMENS

20.3W


WFL

SC: 1.2

LPW: 67

MAXIMUM PERFORMANCE (-2000L SERIES)

Cone of Light ▲




Dist.	FC	Dia.
6	14.0	7.1
8	7.9	9.5
10	5.0	11.9
12	3.5	14.3
14	2.6	16.7
16	2.0	19.0

6"

IP66 Downlight



LRR-06120-2000L  
LRR-06120-1500L  
LRR-06120-1100L



1555 LUMENS

20.3W


WFL

SC: 1.1

LPW: 77

MAXIMUM PERFORMANCE (-2000L SERIES)

Cone of Light ▲




Dist.	FC	Dia.
6	21.8	6.4
8	12.3	8.6
10	7.8	10.7
12	5.4	12.9
14	4.0	15.0
16	3.1	17.2

6"

Ligature / Vandal



LRV-06121-2000L  
LRV-06121-1500L  
LRV-06121-1100L



1555 LUMENS

20.3W


WFL

SC: 1.1

LPW: 77

MAXIMUM PERFORMANCE (-2000L SERIES)

Cone of Light ▲



Dist.	FC	Dia.
6	21.8	6.4
8	12.3	8.6
10	7.8	10.7
12	5.4	12.9
14	4.0	15.0
16	3.1	17.2


▲ Cone of Light Key  
Dist. Distance (Ft.) from fixture  
FC Footcandles at nadir (0°)  
Dia. Circle of light at 50% of FC  
Dia. (in ft.) shown is where FC value is half the FC at nadir.

4"

Wall Washes



**LRR-04137-2000L**  
**LRR-04137-1500L**  
**LRR-04137-1100L**




**1463 LUMENS**

**20.1W**

LPW: 73


MAXIMUM PERFORMANCE (-2000L SERIES)



6"



**LRR-06139-2000L**  
**LRR-06139-1500L**  
**LRR-06139-1100L**




**2133 LUMENS**

**20.3W**

LPW: 105

MAXIMUM PERFORMANCE (-2000L SERIES)




4"

Downlight



**LRS-04142-2000L**  
**LRS-04142-1500L**  
**LRS-04142-1100L**



**2087 LUMENS**


**20.2W**

**WFL**

SC: 1.2

LPW: 103

MAXIMUM PERFORMANCE (-2000L SERIES)



**Cone of Light ▲**


Dist.	FC	Dia.
6	29.9	7.1
8	16.8	9.5
10	10.8	11.9
12	7.5	14.2
14	5.5	16.6
16	4.2	19.0

4"

Wall Wash



**LRS-04172-2000L**  
**LRS-04172-1500L**  
**LRS-04172-1100L**




**1956 LUMENS**

**20.1W**

LPW: 97

MAXIMUM PERFORMANCE (-2000L SERIES)




6"

Downlight



**LSR-06173-2000L**  
**LSR-06173-1500L**  
**LSR-06173-1100L**



**1629 LUMENS**


**20.2W**

**WFL**

SC: 1.1

LPW: 81

MAXIMUM PERFORMANCE (-2000L SERIES)



**Cone of Light ▲**

Dist.	FC	Dia.
6	25.6	6.3
8	14.4	8.5
10	9.2	10.6
12	6.4	12.7
14	4.7	14.8
16	3.6	16.9


**▲ Cone of Light Key**  
**Dist.** Distance (Ft.) from fixture  
**FC** Footcandles at nadir (0°)  
**Dia.** Circle of light at 50% of FC  
 Dia. (in ft.) shown is where FC value is half the FC at nadir.

**12"**

Downlight



**LSR-12184-1500L**  
**LSR-12184-1100L**



MAXIMUM PERFORMANCE (-1500L SERIES)


**1422 LUMENS**

**14.8W**

**WFL**

SC: 1.2

LPW: 96



**Cone of Light ▲**


Dist.	FC	Dia.
6	20.1	7.3
8	11.3	9.7
10	7.2	12.1
12	5.0	14.5
14	3.7	16.9
16	2.8	19.4

**6"**

Direct / Indirect\*



**LWR-06191-2000L**  
**LWR-06191-1500L**  
**LWR-06191-1100L**



MAXIMUM PERFORMANCE (-2000L SERIES)

**DIRECT / INDIRECT**


**1633 / 1167 LUMENS**

**40.2W †**

**WFL**

SC: 1.1

LPW: 70



**Cone of Light ▲**

Dist.	FC	Dia.
6	25.5	6.4
8	14.4	8.5
10	9.2	10.6
12	6.4	12.7
14	4.7	14.8
16	3.6	17.0

**▲ Cone of Light Key**  
Dist. Distance (Ft.) from fixture  
FC Footcandles at nadir (0°)  
Dia. Circle of light at 50% of FC  
Dia. (in ft.) shown is where FC value is half the FC at nadir.

\* Direct/Indirect product number displays downlight lumens.

† Total system watts shown

## Available Lumen Packages

<b>Lumen Package:</b>	-2000L Nominal 2000 lumens (20W)
<b>MUST SPECIFY</b>	-1500L Nominal 1500 lumens (15W)
	-1100L Nominal 1000 lumens (11W)

## Options

See specification sheets at [www.kirlinlighting.com](http://www.kirlinlighting.com) for option availability and details.

### LED Power Supply

- 97 Other voltage ballast; Consult factory
- EI Remote emergency inverter for 100% rated lumen output; Run time: 90+ minutes; 120 or 277V, 60 Hz input only; Specify voltage; Not for use with -FD or -FS

### LED Color (CCT)

- 30K 3000°K color temperature instead
- 41K 4100°K color temperature instead

### Lenses and Trims

- 25 Vandal/ligature resistant trim, hardware and lensing
- 31 White enamel (flange only)
- 32 White oversize trim extender; Specify O.D.
- 35F Silver enamel (flange only)
- 35T Silver enamel (complete trim)
- 37F Dark bronze enamel (flange only)
- 37T Dark bronze enamel (complete trim)
- 38F Black enamel (flange only)

- 38T Black enamel (complete trim)
- 45 Gasket between trim and ceiling
- 70T Clear semi-specular SofTex™ (complete trim)
- 94 Custom color/finish; Specify; Consult factory
- BG Kirlin BioGard™ anti-microbial finish (white only)
- BN Brushed satin nickel finish
- CF Custom color filter (Rosco); Specify
- I65 IP65 rated trim and lens
- WA White acrylic (flat) diffuser instead

### Recessed Housings

- 79 Extension collar for ceilings up to 2" thick
- RH Residential mounting hardware instead; Suitable for wood joist spacings 14 1/8" - 25 7/8"

### Surface Housing Finishes

- 35 Silver enamel finish
- 37 Dark Bronze enamel finish
- 38 Black enamel finish
- 94 Custom color/finish; Specify; Consult factory

### Surface/Pendant/Wall Bracket Mounting

- 54 Safety cable through pendant stem and 12" beyond; Use with -PM
- 80 2" collar for mounting beneath surface outlet box; 1/2" T.S. KO's; Must add Option -89 for wet label listing
- 87 Custom pendant/wall bracket length; Specify length; Also use with Option -PM or -WB
- 88 Swivel canopy for sloped ceilings up to 40°; Use with Option -PM
- 89 Sealed top WeatherCap™ for Wet Label wall bracket or pendant mounts
- ASB Aircraft cable pendant mount; black straight cord; 48" or see -87; No wet label listing
- ASW Aircraft cable pendant mount; white straight cord; 48" or see -87; No wet label listing
- PM Pendant mount instead; 48" stem plus 4" offset; Also see Option -87; Must add Option -89 for wet label listing
- WB Wall-bracket mount instead; Must add Option -89 for wet label listing; Also see -87

### Other

- 84 Fixture wired for two circuits instead of one; Also see Option -FD
- 99 Special modification; Consult factory
- FD Dual in-line fusing for use with Option -84 Not for use with Option -EI
- FS Single in-line fuse; Not for use with Option -EI
- NAT Modified for natatorium use