

Pendant Open
PAR Lamp "Pulse Start"
Cylinders: 39 to 70 Watt

THIS PRODUCT IS NO LONGER AVAILABLE

6" 39W **HPR-06206**
6" 70W **HPR-06207**
6" 70W **HPR-06208**

Features

Lamp

- Designed for metal halide PAR and E-lamps. See chart below for standard and optional lamps and wattages.
- See Option -43 and chart below for lower wattage.

Socket

- Vertical. Medium base. Pulse start.
- Glazed porcelain.
- Nickel-plated brass screw shell. Silicone leads.

Reflector

- Self-flanged clear or Alzak® finish.
- Fourteen optional hood or finish available.

Ballast Assembly: Specify Voltage

- Core and coil ballast supplied as standard.
- Premium Class H; High reactance for 120 volt, linear reactor for 277 volt.
- Capacitor and ignitor supplied.
- Low (-37) and medium (-38) ballasts available. See options.
- Cool, long-life. Silicone leads.
- Pulse start. Rewindable. Not for use in wet, damp or dry locations.
- Seamless white acrylic enameled aluminum.
- No visible vinder hardware.

- Rustproof: Exceeds 1000 hour ASTM 5% salt spray test.

Installation

- Pendant mount. 1/8" T.S. x 18".
- For custom length or swivel canopy mount for sloped ceilings, see Options -87, -88.
- Wall bracket mount available. (See Option -WB)
- Indoor or outdoor for covered ceiling use. (See Option -89)

UL, C-UL (Canada) Listings

- Wet, damp or dry locations, covered ceilings. (See Option -89)

Warranty

- Complete standard fixture, including ballast.

**Please consult
QUOTATIONS
for the best alternative.**

Wattage / Lamp Availability

Catalog No.	Designed For:				Option-43: Lower Wattage	Fixture Style
	Standard Lamp	Optional Lamp(s)				
HPR-06206	39 PAR 30	30° MFL	10° SP	—	—	Open PAR DL
HPR-06207	70 PAR 30	40° MFL	10° SP	65° FL	39	Open PAR DL
HPR-06208	70 PAR 38	25° MFL	15° NSP	65° FL	—	Open PAR DL

Options

Sources and Ballasts

- 39 Remote (10' max.) electronic dimming ballast instead, for pulse start metal halide. Consult factory for wattage and voltage availability.
- 96 Remote (15' max.) electronic MH ballast instead. Consult factory for internal mounting.

Wattage and Voltage

- 43 Lower wattage: See Option -43 chart above for available lower wattages. Specify voltage.
- 120 120 volt, 60 Hz. ballast.
- 277 277 volt, 60 Hz. ballast.
- 347 347 volt, 60 Hz. ballast. Consult factory for dimming or electronic.
- 97 Other voltage ballast instead. Consult factory.

Lamps (See Chart)

- LP With lamp. Choose standard lamp shown above or specify wattage, beam spread, style (PAR 30, PAR 38), brand and color temperature.

Reflectors and Trims (Self-Flanged)

- 16 Champagne Gold specular Alzak reflector. (CP x .98)
- 30 All White reflector. (CP x .98)
- 63 Dune specular Alzak reflector. (CP x .97)
- 69 Wheat specular Alzak reflector. (CP x .97)
- 70 SoftTex Clear softly etched reflector. (CP x .98)
- 71 SoftTex Dune softly etched reflector. (CP x .95)
- 72 Black specular Alzak reflector. (CP x .87)
- 77 SoftTex Pewter softly etched reflector. (CP x .90)
- 90 SoftTex Champagne Gold softly etched reflector. (CP x .96)
- 91 SoftTex Wheat softly etched reflector. (CP x .95)
- 92 Umber specular Alzak reflector. (CP x 92)
- 93 Pewter specular Alzak reflector. (CP x .95)
- 94 Custom color reflector. Consult factory.
- OG OptiGroove black seamless tapered aluminum reflector. White trim. (CP x .90)

Luminaire (Housing) Finishes

- 35 Natural Aluminum enameled luminaire finish instead.
- 36 Gold enameled luminaire finish instead.

- 37 Dark Bronze enameled luminaire finish instead.
- 38 Black enameled luminaire finish instead.
- 94 Custom color luminaire finish. Consult factory.

Mounting Options

- 54 Safety cable through pendant stem. 12" longer than specified stem length. Anchored to fixture. Use with Option -PM.
- 87 Custom -PM length. Specify up to 4 feet or consult factory for longer lengths with couplers.
- 88 Swivel canopy for sloped ceilings up to 45°. Earthquake rated. Use with Option -PM.
- 89 Sealed top feature prevents moisture and insect intrusion from above in outdoor or high humidity areas. Must add to pendant mount or Option -WB for Wet Label listing.
- WB Wall bracket mount instead. Also see Option -89.

Other Options

- 99 Special modification. Consult factory.

