


CATALOG #	TYPE	
JOB NAME	WATTAGE	VOLTAGE

6" 1 A19 100 WATT MAXIMUM

ISR-06141

Versatile Regressed Lens Cylinder



Specifications

Lamp / Socket

- Designed for one vertical frosted incandescent lamp (by others): 100W maximum A19.
- Dimmable (controls by others).
- Glazed porcelain medium base socket.

Reflector

- Specular Alzak® aluminum.

Trim Assembly

- Tapered aluminum one piece black OptiGroove with white flange or all white smooth self-flanged trim (Option -40).
- Regressed tempered prismatic C#73 glass lens.
- Optional lenses and trims available.

Aluminum Housing

- Seamless white acrylic enameled. Rustproof. Exceeds 1000 hour ASTM 5% salt spray test.

- No visible cylinder hardware.
- Lightweight: Minimizes ceiling load.
- Cool operation: Extends component life.

Installation

- Center point mounting for snug fit to ceiling. Mounting hardware included.
- 2" collar for surface J-box mount (Option -80).
- Pendant or wall bracket mount available. (See Options -PM, -WB).
- Indoor or outdoor for covered ceiling use. For wet label in uncovered areas, add Option -89.

UL C-UL (Canada) Listings

- Wet, damp or dry locations, covered ceilings.
- With Option -89: Wet, damp or dry locations, uncovered areas.
- 90°C minimum supply wire.


Three Year Limited Warranty

- Complete standard fixture.

Surface Round
Regressed
Lens

Performance at a Glance


ISR-06141



Cone of Light Key

- Ft.** Distance from fixture
- FC** Footcandles at nadir (0°)
- Dia.** Circle of light at 50% of FC



* Dia. (in ft.) shown is where FC value is half the FC at nadir.



Representative Views:

(Left) With optional pendant mount (Option -PM)

(Right) With optional wall bracket (Option -WB)



Cone of Light*

Dist.	FC	Dia.
6	24.3	4.8
8	13.7	6.5
10	8.8	8.1
12	6.1	9.7
14	4.5	11.3
16	3.4	12.9

THE KIRLIN COMPANY

3401 EAST JEFFERSON AVENUE • DETROIT, MICHIGAN 48207-4232
(313) 259-6400 • Fax: (313) 259-9409 OR (313) 259-3121 • www.kirlinlighting.com

TUNGSTEN HALOGEN &
INCANDESCENT LIGHTING

MAXIMUM WATTAGE

100

CATALOG NUMBER

ISR-06141


DUE TO OUR CONTINUING EFFORT TO IMPROVE PRODUCTS, TECHNICAL INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE.

Alzak® is a registered trademark of ALCOA.

Detailed Photometry - Installed Fixture

Photometry from I.T.L., Boulder, CO

ISR-06141 (100 Watt)



CANDLEPOWER DISTRIBUTION					
	0.0	22.5	45.0	67.5	90.0
0	875	875	875	875	875
5	856	856	856	856	856
15	713	713	713	713	713
25	474	474	474	474	474
35	253	253	253	253	253
45	118	118	118	118	118
55	52	52	52	52	52
65	20	20	20	20	20
75	3	3	3	3	3
85	0	0	0	0	0
90	0	0	0	0	0

COEFFICIENTS OF UTILIZATION							
RF	20						
	80				50		
	RW	70	50	30	10	50	30
1	53	51	50	49	48	47	47
2	50	47	45	43	42	41	40
3	47	43	41	39	38	37	36
4	44	40	37	35	34	33	32
5	42	37	34	32	31	30	29
6	39	35	32	29	28	27	26
7	37	32	29	27	26	25	24
8	35	30	27	25	24	23	22
9	33	28	26	24	23	22	21
10	32	27	24	22	21	20	19

ITL TEST #47000

THIS FIXTURE IS NO LONGER AVAILABLE FOR REPLACEMENT CONSULT FACTORY

Options

Lenses and Trims

- 18 Opal flat glass. Not enameled. Diffusing.
- 20 White 1/2" cube eggcrate aluminum louver.
- 40 White grooveless flare trim. (CP x 1.10)
- 45 Gasket between housing and trim.
- 46 Gasket between trim and lens.
- FR Fresnel tempered glass lens.

Luminaire (Housing) Finishes

- 35 Natural aluminum acrylic enamel.
- 36 Gold acrylic enamel.
- 37 Dark Bronze acrylic enamel.

- 38 Black acrylic enamel.
- 94 Custom color/finish. Specify. Consult factory.

Mounting

- 54 Safety cable through pendant stem and 12" beyond. Use with -PM.
- 80 2" collar for mounting beneath surface outlet box. 1/2" T.S. KO's.
- 87 Custom pendant / wall bracket length. Specify. (Pendant length up to 4' or consult factory.) Use with Options -PM or -WB.
- 88 Swivel canopy for sloped ceilings up to 40°. Earthquake rated. Use with -PM.

- 89 Sealed top WeatherCap. Must add to Options -PM and -WB for wet label listing.
- PM Pendant mount. 3/8" T.S. x 18" stem or see Option -87. Must add Option -89 for wet label listing. Also see -88.
- QM QuickConnect mount for indoor (damp or dry) use only.
- WB Wall bracket mount. Must add Option -89 for wet label listing.

Other

- 99 Special modification. Consult factory.

SUBMITTAL DATA

APPROVAL STAMP

JOB NAME _____
 TYPE _____
 WATTAGE _____ VOLTAGE _____
 CATALOG NUMBER _____

LIMITED WARRANTY: CATALOGED KIRLIN FIXTURES ARE WARRANTED FREE OF DEFECTS IN WORKMANSHIP OR MATERIAL FOR THREE YEARS FROM DATE OF PURCHASE. INSTALL TO N.E.C. IN NORMAL USE. Manufacturer of the option will replace or repair such fixture or refund the purchase price on presentation of proof of purchase and defective fixture at the offices of manufacturer within three years of original shipment. Liability of manufacturer is limited to the foregoing and manufacturer shall not be liable for any other damages, direct or indirect, sustained or suffered by purchaser or any person. This warranty is subject to the buyer in place of all other warranties, expressed or implied. Seller does not warrant as to merchantability or fitness for a particular use, nor will any oral statement constitute a warranty or amend this specific warranty. Abnormal use, abuse of the fixture, improper installation, or repair, or modification of the fixture without prior written authorization from the manufacturer will render the warranty void.