

| CATALOG # | | TYPE | |
|-----------|---------|---------|--|
| JOB NAME | WATTAGE | VOLTAGE | |

Wayfinding Series

Mini-Rectangle 3" x 5" Nightlight • LED 50,000 Hour Rated • Type IC • Optional LED Filter Colors

Specifications

- White module (colored filters optional)
- 3500°K standard
- · 4 system watts energy efficient, uniform, cool

LED Power Supply/Driver

- Max 13 volt DC and 4 watt fixed output; electronically stabilized
- Minimum operating temperature -4°F (-20°C)
- 120-277 volt standard: load insensitive

Lens

Clear linear tempered glass lens sealed to trim

Faceplate

- Rustproof aluminium trim
- White finish standard; optional colors
- Optional (white only) antimicrobial Kirlin BioGard™ finish; see Option -BG
- Secured to housing with two screws and captive nuts
- Removable for servicing

Housing: Shallow 31/2" Depth

 2" x 3" x 3½" standard U. L. listed galvanized steel outlet box

Installation

- Recesses indoor or outdoor, covered locations; versatile 31/2" depth
- Mounting holes on top and bottom

LNT-03092



UL, C-UL (Canada) Listings

- · Damp or dry locations
- Type IC; approved for direct contact with insulation

FIVE YEAR Limited Warranty

· Complete standard fixture










Options and Ordering Configuration

(Example: LNT-03092-BL-37-26)


| Required | Optional | | | | |
|-----------|---|--|---|---|--|
| Model | Voltage/Battery Pack | Filter Colors | Faceplate Finishes | Other Options | |
| LNT-03092 | | | | | |
| | (Blank): Universal 120-277 V | (Blank): None | (Blank): Standard white finish | (Blank): None | |
| | -97: Other voltage input; consult factory -EI: Remote emergency inverter for 100% of rated lumens; Run time: 90+ minutes; 120 or 277V, 60Hz input only; specify voltage | -BL: Blue filter -GE: Green filter -OR: Orange filter -RA: Red/Amber filter -YE: Yellow filter -CF: Custom color filter (Rosco); specify | -35: Silver (natural aluminum) acrylic enamel -37: Dark bronze acrylic enamel -38: Black acrylic enamel -BG: BioGard™ anti-microbial white -BKBG: BioGard™ anti-microbial black -94: Custom color; consult factory -94BG: BioGard™ anti-microbial custom color finish | -26: Faceplate secured to housing with two center pin tamperproof screws; Tamperproof too included -99: Special modification; consult factory | |

Performance


Footcandle Performance Opposite Fixture Installed Top View



Dimensions



LED Filter Colors



31/2"