

CATALOG #	TYPE	
JOB NAME	WATTAGE	VOLTAGE

# Latitudes Series

## Super Shallow 2¾" Depth Downlight • LED

Up to 60,000 Hour Rated Life • Open Appearance • Wet Listed  
LM-79 Certified • LM-80 Qualified

# LRR-05438



## Specifications

### Delivered System Performance

- Nominal Lumens: **Must Specify**  
**Non-IC -2500L**
- Select trim & beam distribution: see chart
- Select color (CCT): see chart; 80+ CRI standard; Option -HC for 90+ (15% lumen loss)
- 60,000 Hour Rated Life (L70)

### Thermal Protection: SPECIFY VOLTAGE

- Thermal protector for insulation detection per UL/NEC. Must specify input voltage

### Thermal Management System

- Aluminum heat sink and components for cool operation, long life, and low maintenance

### LED Driver - INTERNAL

- Indoor/Outdoor: -30°C to 60°C (-22°F to 140°F)
- 0-10V CCR 10% dimming standard
- 120-277V / 50-60 Hz standard; load insensitive

### Trim Assembly

- Seamless tapered aluminum self-flanged trim with white finish (field paintable). 3.25" top aperture
- Regressed tempered prismatic spread lens

### Acrylic Enameled Aluminum Housing

- Rustproof and corrosion resistant: exceeds 1000 hour ASTM 5% salt spray test
- Shallow depth fits restricted plenums
- Cool operation extends component life
- Modular design; visible and fully serviceable through aperture
- Built-in plaster flange

### Outlet Box (Galvanized)

- UL Listed, 14GA, insulated, removable cover
- ½" and ¾" knockouts

### Installation & Hardware

- Indoor/outdoor in ceilings up to 1½" thick or see Option -79
- Compatible with fire rated enclosures (by others)
- 27" hanger bars & adjusting brackets (2) supplied

### UL, C-UL (Canada)

- UL Listed: wet, damp or dry locations, covered ceilings
- Through-branch conductors (4 #12 AWG 90°C)

### IEC & FCC Compliance

- Meets IEC/EN 60601-1-2 electromagnetic compatibility standard for medical electrical equipment
- FCC Part 15 certified for EMI/RFI emissions

### FIVE YEAR Limited Warranty

- Complete standard fixture





## Options and Ordering Configuration

(Example: LRR-05438-2500L-120-MFL-30K-45-NAT)

Must Specify					Optional			
Model	Lumens	Volts	Beam	CCT† & CRI	Driver Options	Emergency Options	Trim Options	Other Options
LRR-05438	-2500L	-120 -277 -97†: Other Voltage	(Blank): MFL  -MFL	(Blank): 3500K, 80+ CRI  <b>80+ CRI*</b> -27K: 2700°K -30K: 3000°K -35K: 3500°K -41K: 4000°K -50K: 5000°K  *Note: Lumen Factor = 0.93 for -27K  <b>90+ CRI**</b> -27K-HC: 2700°K -30K-HC: 3000°K -35K-HC: 3500°K -41K-HC: 4000°K -50K-HC: 5000°K  **Note: Lumen Factor = 0.79 for -27K-HC; All Others = 0.85; Consult Factory	(Blank): Standard 0-10V CCR 10% dim  -D1: 0-10V 1.0% dim  -ECO: Digital driver for Lutron EcoSystem controls. Dims to 1% or consult factory. Requires 5" deep housing, including plaster flange depth	(Blank): None  -ERH: Remote emergency battery pack; Delivers 1000 lumens; CEC Compliant; Run time: 90+ minutes	(Blank): Tapered aluminum self-flanged trim with white finish; regressed tempered prismatic spread lens  <b>Trim Finishes</b> -30F: White enamel (flange only) -35T: Silver enamel (complete trim) -62T: Clear specular (complete trim) -94: Custom color; consult factory  <b>Other Trim Features</b> -23: Frosted microprismatic lens -32: White trim extender, specify OD -45: Gasket between trim & ceiling -DF: Electrically isolated "dead front" gasketed trim. Also requires option -45 -WA: White acrylic lens; will produce wide flood distribution	(Blank): None  <b>Mounting</b> -79: Extension collar for ceilings up to 2" thick  <b>Other Options</b> -99: Special modification; consult factory -FS: Fused primary; One per fixture -NAT: Modified for natatorium use -SH: Sealed housing and junction box -TA: Top access for servicing from above ceiling


## Dimensions



\* See notes on page 1 for additional info on Lumen Factors

## Photometry - Installed Complete Fixture

LM-79 IESNA Certified Photometry from Independent Lab



LED manufacturers maintain a tolerance of +/-7% on flux (lumens) and power (electrical) measurements.

▲ **Cone of Light Key**  
 Dia. (in ft.) shown is where FC value is half the FC at nadir.  
**Dist.** Distance (Ft.) from fixture  
**FC** Footcandles at nadir (0°)  
**Dia.** Circle of light at 50% of FC