JOB NAME _

FOR POURED CONCRETE CEILINGS

DUAL REFLECTOR ELLIPSOIDAL DOWNLIGHT

Features

KIRLIN

Lamp

• Designed for: 150 watt maximum A21.

Socket


- Horizontal. Medium base.
- Glazed porcelain.
- Nickel-plated brass screw shell. Silicone leads.

Reflectors

- Upper: Compound ellipsoidal specular Alzak® aluminum.
- Lower: Low brightness parabolic specular Alzak aluminum, self-flanged. Fully gasketed.
- Optional colors or lens listed in Options

Housing

- 16 GA. galvannealed steel, red bxide rustproof primer coal with black ename finish.
- Fully gasketed.



Entire luminaire serviced through removable reflector.

Outlet Box

- Prewired 14 GA (NEC) galvanized steet, UL listed.
- 1/2" and 3/4" knockouts.

Installation

concrete ceilings. 90° feed wire required.


JL, C-UL (Canada) Listings


- For use in poured concrete ceilings.
- Through-branch circuit conductors (6#12).

Three Year Limited Warranty

Complete standard fixture

APPROVAL STAMP





Options

- -15 Tempered prismatic C#73 flat glass on upper reflector. Spread distribution.
- -16 Champagne Gold anodized Alzak® lower reflector, self-flanged.
- -30 White lower reflector, self-flanged.
- -31 White flange (only) on lower reflector.
- -72 Black anodized Alzak lower reflector, self-flanged.
- -92 Umber anodized Alzak lower reflector, self-flanged.
- -93 Pewter anodized Alzak lower reflector, self-flanged.
- 94 Custom color lower reflector. Consult factory.
- -99 Special modification. Consult factory.
- -LP With lamp. Specify wattage.
- OG OptiGroove black seamless tapered aluminum lower reflector. White trim, self-flanged.

THE KIRLIN COMPANY

3401 EAST JEFFERSON AVENUE • DETROIT, MICHIGAN 48207-4232 (313) 259-6400 • FAX: (313) 259-9409 or (313) 259-3121 • www.kirlinlighting.com

INCANDESCENT LIGHTING LAMP MAXIMUM WATTAGE

CATALOG NUMBER

A21

150

RR30697