

CATALOG #	TYPE	
JOB NAME	WATTAGE	VOLTAGE

Symphony Remote Driver Series

Lensed 7" Wall Wash • LED

Up to 60,000 Hour Rated Life (L70) • Wet Location
LM-80 Qualified • LM-79 Certified Photometry

SRR-07618



Specifications

Delivered System Performance

- Lumen Series: **Must Specify**
 - 6500L: 6500 nominal lumens (74W)
 - 5000L: 5000 nominal lumens (55W)
 - 4000L: 4000 nominal lumens (42W)
 - 2500L: 2500 nominal lumens (35W)
- Color temperature: 3500°K standard; Optional: -27K, -30K, -41K or -50K
- CRI: 80+ standard; Optional: -HC (90+)
- 60,000 hour rated life (L70)
- Fully sustainable: removable for servicing
- Center beam optics positioned at 25°

Thermal Management System

- All aluminum heat sink, components and housing maximize cool operation and long life while minimizing maintenance

Remote Power Supply Required

- For 0-10V use **SYM-CABNT**
- For DMX with RDM use **SYM-DMXPS**
- The **Symphony Configurator** can help determine the necessary components

SmartPower™ Battery Backup

- EMI-21220** for emergency power
- See specification sheet; order separately

Trim

- Clear specular aluminum trim
- Self-flanged, low glare angle-cut cone; prismatic spread lens above
- Optional colors and finishes available

Acrylic Enamelled Aluminum Housing

- Rustproof and corrosion: Exceeds 1000 hour ASTM 5% salt spray test
- Shallow depth fits restricted plenums
- Cool operation: Extends life of all components
- Fully sustainable: Entire luminaire, including LED light engine, easily visible and serviced through aperture
- Built-in plaster flange

Outlet Box

- UL listed J-box with insulated removable cover; prewired 14 GA (NEC) with 1/2" and 3/4" knockouts

Installation

- Requires minimum 16 AWG shielded twisted pair wire from driver to fixtures
- Maximum cable run from driver to fixture is 250'**

- Recesses in ceilings up to 1 1/8" thick
- Compatible with fire rated enclosures (by others)
- 27" galvanized hanger bars with adjustable mounting brackets (2) supplied

UL, C-UL (Canada) Listings

- Wet, damp, dry locations, covered ceilings
- 2500L (only): Type IC - for direct contact with insulation

FCC Compliance

- FCC Part 15 certified for EMI/RFI emissions

FIVE YEAR Limited Warranty

- Complete standard fixture (must be used with SYM-CABNT or SYM-DMXPS)




Options and Ordering Configuration

(Example: SRR-07618-6500L-30K-45)

Must Specify		Optional		
Model	Lumens	Color Temp. (CCT)	Lens & Trim	Other Options
SRR-07618				
	<ul style="list-style-type: none"> -6500L -5000L -4000L -2500L 	<ul style="list-style-type: none"> (Blank): 3500°K -27K: 2700°K instead -30K: 3000°K instead -41K: 4000°K instead -50K: 5000°K instead -HC: 90+ CRI instead 	<ul style="list-style-type: none"> (Blank): Clear specular trim; lens above -30T: White enamel (complete trim) -30F: White enamel (flange only) -32: White oversize trim ring; specify O.D. -37F: Dark bronze enamel (flange only) -38F: Black enamel (flange only) -45: Gasket between trim flange and ceiling -70T: Clear semi-specular SofTex™ (complete trim) -94: Custom color/finish; specify; consult factory 	<ul style="list-style-type: none"> (Blank): None -99: Special modification; consult factory -AT: Air tight version; meets ASTM E283 restricted airflow of 2 CFM maximum -RH: Residential mounting hardware instead; suitable for wood joist ceilings with spacing from 14 1/8" to 25 7/8" with 5/8" vertical adjustability -SH: Sealed housing and junction box for -6500L or -5000L; see Option -AT for use with -2500L

Dimensions



Photometry - Installed Complete Fixture


Photometry from I.T.L., Boulder, CO
 and UL Verification Services, Allentown, PA

LM-79 IESNA Certified Photometry from Independent Lab

-6500L Performance

Lumens: **5516**
 LPW: **75**
 Efficiency: **77.7%**
 ITL Test: **86451**

WALL > ----- 0°
 ----- 90°
 ----- 180°




Total System Watts 73.3

DISTANCE FROM CEILING IN FEET	SINGLE FIXTURE				MULTIPLE FIXTURES						
	1'	2'	3'	4'	2' CENTERS	3' CENTERS	3' CENTERS	3' CENTERS			
	FIXTURE INSTALLED 2' FROM WALL Footcandle Distribution on Wall Surface										
1	122.0	56.5	13.3	4.3	2.1	158.0	158.0	158.0	132.0	60.3	132.0
2	295.0	180.0	46.5	12.4	4.3	398.0	398.0	398.0	324.0	201.0	324.0
3	217.0	159.0	70.2	22.8	7.6	379.0	379.0	379.0	266.0	230.0	266.0
4	132.0	107.0	61.0	27.7	11.0	283.0	283.0	283.0	192.0	185.0	192.0
5	80.5	69.3	46.1	25.5	12.7	207.0	207.0	207.0	138.0	137.0	138.0
6	51.2	45.8	33.6	21.5	12.4	156.0	156.0	156.0	104.0	103.0	104.0
7	34.4	31.5	24.9	17.6	11.4	121.0	122.0	122.0	80.2	79.5	80.2
8	24.4	23.1	19.2	14.5	10.2	99.5	99.8	99.8	64.6	65.8	64.6
9	18.9	18.2	15.8	12.6	9.4	85.7	86.0	86.0	55.2	56.8	55.2

-5000L Performance

Lumens: **4761**
 LPW: **83**
 Efficiency: **80.1%**
 ITL Test: **87777**

WALL > ----- 0°
 ----- 90°
 ----- 180°




Total System Watts 57.5

DISTANCE FROM CEILING IN FEET	SINGLE FIXTURE				MULTIPLE FIXTURES						
	1'	2'	3'	4'	2' CENTERS	3' CENTERS	3' CENTERS	3' CENTERS			
	FIXTURE INSTALLED 2' FROM WALL Footcandle Distribution on Wall Surface										
1	80.3	36.8	8.9	3.1	1.6	106.0	106.0	106.0	88.6	40.3	88.4
2	244.0	139.0	35.0	8.7	3.1	322.0	322.0	322.0	265.0	153.0	265.0
3	198.0	145.0	55.4	17.0	5.6	321.0	322.0	322.0	236.0	198.0	236.0
4	119.0	101.0	54.2	21.5	8.2	250.0	250.0	250.0	165.0	170.0	165.0
5	71.0	64.2	42.9	21.5	9.7	184.0	184.0	184.0	119.0	125.0	119.0
6	45.7	42.0	31.8	19.1	10.1	139.0	140.0	140.0	91.5	92.4	91.5
7	31.6	29.2	23.5	16.1	9.7	109.0	110.0	110.0	72.1	71.7	72.1
8	23.1	21.7	18.1	13.5	9.0	89.4	90.5	90.5	59.0	59.5	59.0
9	18.4	17.5	15.1	11.8	8.5	78.5	78.8	78.8	51.0	52.0	51.0

-4000L Performance

Lumens: **3828**
 LPW: **89**
 Efficiency: **80.3%**
 ITL Test: **88286**

WALL > ----- 0°
 ----- 90°
 ----- 180°




Total System Watts 43.0

DISTANCE FROM CEILING IN FEET	SINGLE FIXTURE				MULTIPLE FIXTURES						
	1'	2'	3'	4'	2' CENTERS	3' CENTERS	3' CENTERS	3' CENTERS			
	FIXTURE INSTALLED 2' FROM WALL Footcandle Distribution on Wall Surface										
1	64.6	29.6	7.1	2.5	1.3	85.2	85.3	85.3	71.2	32.5	71.1
2	196.0	112.0	28.1	7.0	2.5	259.0	259.0	259.0	213.0	123.0	213.0
3	159.0	116.0	44.5	13.7	4.5	258.0	259.0	259.0	190.0	159.0	189.0
4	95.6	80.8	43.6	17.3	6.6	201.0	201.0	201.0	133.0	136.0	133.0
5	57.0	51.6	34.5	17.3	7.8	148.0	148.0	148.0	95.7	101.0	95.7
6	36.7	33.8	25.5	15.4	8.1	112.0	112.0	112.0	73.6	74.3	73.6
7	25.4	23.4	18.9	12.9	7.8	87.3	88.1	88.1	58.0	57.7	57.9
8	18.6	17.5	14.6	10.9	7.3	71.9	72.8	72.8	47.4	47.9	47.4
9	14.8	14.1	12.1	9.5	6.8	63.1	63.3	63.3	41.0	41.8	41.0

-2500L Performance

Lumens: **2810**
 LPW: **80**
 Efficiency: **75.6%**
 ITL Test: **87776**

WALL > ----- 0°
 ----- 90°
 ----- 180°



Total System Watts 35.2

DISTANCE FROM CEILING IN FEET	SINGLE FIXTURE				MULTIPLE FIXTURES						
	1'	2'	3'	4'	2' CENTERS	3' CENTERS	3' CENTERS	3' CENTERS			
	FIXTURE INSTALLED 2' FROM WALL Footcandle Distribution on Wall Surface										
1	50.6	24.5	5.8	1.8	0.9	66.9	67.0	67.0	55.5	27.0	55.3
2	143.0	82.6	22.8	5.9	2.1	193.0	193.0	193.0	157.0	92.9	157.0
3	114.0	83.3	32.4	10.7	3.8	190.0	190.0	190.0	138.0	114.0	138.0
4	67.9	57.2	30.9	12.6	5.2	143.0	144.0	144.0	95.3	97.3	95.3
5	40.9	36.6	24.3	12.4	5.8	106.0	106.0	106.0	68.8	71.9	68.8
6	26.3	24.1	18.1	10.9	5.9	80.4	80.5	80.5	52.9	53.4	52.9
7	18.1	16.8	13.4	9.2	5.6	63.0	63.2	63.2	41.5	41.3	41.5
8	13.3	12.5	10.4	7.8	5.2	52.1	52.3	52.3	34.0	34.5	34.0
9	10.6	10.1	8.7	6.8	4.9	45.4	45.6	45.6	29.4	30.1	29.4

LED manufacturers maintain a tolerance of +/-7% on flux (lumens) and power (electrical) measurements.

LIMITED WARRANTY: KIRLIN LIGHTING FIXTURES ARE WARRANTED FREE OF DEFECTS IN WORKMANSHIP OR MATERIAL FOR A PERIOD OF THREE YEARS FROM DATE OF PURCHASE. INSTALLATION MUST BE IN ACCORDANCE WITH THE IESNA LM-79 METHOD. THE WARRANTY DOES NOT COVER DAMAGE TO THE FIXTURE CAUSED BY IMPROPER INSTALLATION, OVERLOADING, OR USE OF INAPPROPRIATE VOLTAGE. THE WARRANTY IS VOID IF THE FIXTURE IS USED IN A MANNER NOT INTENDED BY THE MANUFACTURER. THE WARRANTY IS VOID IF THE FIXTURE IS REPAIRED OR MODIFIED BY ANY OTHER PARTY. THE WARRANTY IS VOID IF THE FIXTURE IS USED IN A MANNER NOT INTENDED BY THE MANUFACTURER. THE WARRANTY IS VOID IF THE FIXTURE IS REPAIRED OR MODIFIED BY ANY OTHER PARTY. THE WARRANTY IS VOID IF THE FIXTURE IS USED IN A MANNER NOT INTENDED BY THE MANUFACTURER. THE WARRANTY IS VOID IF THE FIXTURE IS REPAIRED OR MODIFIED BY ANY OTHER PARTY.

Symphony Driver Modules

Fully Digital Controlled Power Source for LED Luminaires

Mounted in Kirlin's **SYM-CABNT**

Drivers wired in series



Driver Module	Maximum Capacity	Fixture Load Examples
DVR-1400A	Qty 1: 2500L Luminaires	<ul style="list-style-type: none"> • Qty 1: SRR-07618-2500L
DVR-1400B *Not available with DMX dimming	Up to Qty 2: 2500L Luminaires	<ul style="list-style-type: none"> • Qty 1: SRR-07618-2500L • Qty 2: SRR-07618-2500L • Qty 1: SRR-07618-2500L and Qty 1: SRR-07604-2500L
DVR-1050A	Qty 1: 4000L Luminaires	<ul style="list-style-type: none"> • Qty 1: SRR-07618-4000L
DVR-1400B *Not available with DMX dimming	Qty 1: 5000L Luminaires	<ul style="list-style-type: none"> • Qty 1: SRR-07618-5000L
DVR-1400A	Qty .5: 6500L Luminaires	<ul style="list-style-type: none"> • Qty 1: SRR-07618-6500L requires Qty 2: DVR-1400A