

CATALOG #	TYPE	
JOB NAME	WATTAGE	VOLTAGE

10" 2 Triple 32 WATT MAXIMUM

FRV-10076

Attractive and Versatile Vandal Resistant

Features

Lamp

- Designed for two 4-pin triple tube amalgam or quad compact fluorescent lamps: 32/26W triple or 26W quad.

Ballast: Multi-Wattage/Voltage

- Installed electronically protected. For lower wattages: Option -43.
- 120-277 multi-volt; 50/60 Hz. THD < 10%.
- ClickQuick connectors for easy service.
- Single circuit wiring or see Option -84.
- Cold weather -22°F (-30°C).
- End of lamp life protection circuit.
- Internally fused. Also see Option -F1 -F3.

Reflector

- Specular Alzak® aluminum.

Trim / Lens Assembly

- Vandal resistant tapered aluminum, one piece black OptiGrip® with white flange or see Option -40.
- Flush tamper proof hex screws with center pin to secure trim to captive nuts in housing.
- Continuous wiring and four screws secure lens.

- Lens combines 1/4" clear polycarbonate below with prismatic .187" high-strength acrylic.

Aluminum Housing

- Acrylic enameled. Rustproof: Exceeds 1000 hour ASTM 5% salt spray test.
- Lightweight: Minimizes ceiling load.
- Cool operation: Extends component life.

- Built-in plaster frame.

Outlet Box

- Prewired 14 GA (NEC) galvanized steel, UL listed 1/2" and 3/4" knockouts.


Installation

- Pre-drilled holes have spacers in adjustable mounting bracket (2 included).
- Recesses indoor or outdoor in covered locations.

- Tamper proof lens included.
- UL, C-UL (Canada) listed.
- Wet/damp location suitable for use in ceiling.
- Through-bracket conductors (1, 2).

Three Year Limited Warranty

- Complete standard fixture and ballast.



Recessed Round
Vandal Resistant
Regressed Lens
Shallow Plenum


Selected Optional Trim:

- White Grooveless Flare Option -40

THIS PRODUCT IS NO LONGER AVAILABLE

Performance at a Glance


FRV-10076



Please consult

QUOTATIONS

for the best alternative.




(2 Triple 32W)

Cone of Light*

Dist.	FC	Dia.
6	27.8	6.7
8	15.6	9.0
10	10.0	11.2
12	6.9	13.5
14	5.1	15.7
16	3.9	18.0

--- 0° SC 1.1
--- 45° SC 1.2
--- 90° SC 1.3



(2 Quad 26W)

Cone of Light*

Dist.	FC	Dia.
6	10.3	7.1
8	5.8	9.5
10	3.7	11.8
12	2.6	14.2
14	1.9	16.6
16	1.5	18.9

--- 0° SC 1.2
--- 90° SC 1.3
--- 180° SC 1.3

- Cone of Light Key**
- Ft. Distance from fixture
 - FC Footcandles (average)
 - Dia. Circle of light at 50% of FC
 - * Dia. (in ft.) shown is where FC value is half the FC at nadir.

THE KIRLIN COMPANY

3401 EAST JEFFERSON AVENUE • DETROIT, MICHIGAN 48207-4232
(313) 259-6400 • Fax: (313) 259-9409 OR (313) 259-3121 • www.kirlinlighting.com

RENAISSANCE SERIES
COMPACT FLUORESCENT LIGHTING

MAXIMUM WATTAGE

2 Triple 32

CATALOG NUMBER

FRV-10076

DUE TO OUR CONTINUING EFFORT TO IMPROVE PRODUCTS, TECHNICAL INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE.

Alzak® is a registered trademark of ALCOA.

