

Pendant Open and Lensed
"Pulse Start" Downlights
39 to 70 Watt

THIS PRODUCT IS NO LONGER AVAILABLE

Please consult

QUOTATIONS

for the best alternative.

6" 70W
6" 70W
6" 70W

HPR-06209
HPR-06211
HPR-06212

Features

Lamp

- Designed for medium base metal halide E-lamps (HPR-06209, HPR-06211) or T-6 bi-pin (HPR-06212). See chart below for standard and optional wattages.
- See Option -43 and chart below for lower wattage, or HPS availability.

Socket

- Pulse rated. Vertical. Silicone leads.
- Porcelain.
- E-lamp: Nickel plated brass screw shell.
- T-6: G12 bi-pin.

Reflector

- Specular Alzak® aluminum.
- HPR-06209: Self-flanged. Optional finishes.

Trim Assembly (HPR-06211, HPR-06212)

- Seamless tapered black OptiGroove with white self-flanged trim.

- UV absorbing tempered prismatic low brightness C#73 flat glass lens.
- Optional trims and lenses available.

Ballast Assembly: Specify Voltage

- Core and coil ballast supplied as standard.
- Electronic Class II, high inrush for 120V.
- Inductor for 277V.
- Capacitor and ignitor supplied.
- Dimming (-39) and electronic (-96) ballasts available. See Options.
- Socket on Silicone and Pulse Rated.
- Fused primary. Renewable. Not for 480 volt.

- Housing: Clear or white vinyl or anodized aluminum.
- No visible cylinder hardware.

- Cool: Dissipates heat across entire surface.
- Rustproof: Exceeds 1000 hour ASTM 5% salt spray test.

Installation

- Pendant mount. 3/8" T.S. x 18".
- For custom length or swivel canopy mount for sloped ceilings see Options -87, -88.
- Wall bracket mount available. (See Option -WB)
- Indoor or outdoor for covered ceiling use. (See Options -QM, -89)

UL, C-UL (Canada) Listings

- Wet, damp or dry locations, covered ceilings. (See Options -QM, -89)
- See our Limited Warranty
- Complete standard fixture, including ballast.

Wattage Availability

Catalog No.	Lamp/Base	Standard Wattage		Option -43: Lower Wattage		Max. Standby Wattage (-49-65-66-LS)	Fixture Style
		Pulse MH	-24 (HPS)	Pulse MH	-24 (HPS)		
HPR-06209	ED-17/Med	70	—	50	—	—	Open
HPR-06211	ED-17/Med	70	70	50	35-50	—	Lensed
HPR-06212	T-6/G12 bi-pin	70	—	39	—	—	Lensed

Options

Sources and Ballasts

- 24 HPS ballast instead. See wattage chart above for available wattages. Specify voltage.
- 39 Remote (10' max.) electronic dimming ballast instead, for pulse start metal halide. Consult factory for wattage and voltage availability.
- 96 Remote (15' max.) electronic MH ballast instead. Consult factory for internal mounting.

Wattage and Voltage

- 43 Lower wattage: See Option -43 chart above for available lower wattages. Specify voltage.
- 120 120 volt, 60 Hz. ballast.
- 277 277 volt, 60 Hz. ballast.
- 347 347 volt, 60 Hz. ballast. Consult factory for dimming or electronic.
- 97 Other voltage ballast instead. Consult factory.

Lamps (See Chart)

- LP With lamp. Specify source, wattage, color temperature, and clear or coated.

Reflectors and Trims (Self-Flanged) (HPR-06209 only)

- 16 Champagne Gold specular Alzak reflector. (CP x .98)
- 30 All White reflector. (CP x .98)
- 63 Dune specular Alzak reflector. (CP x .97)
- 69 Wheat specular Alzak reflector. (CP x .97)
- 70 SoftTex Clear softly etched reflector. (CP x .98)
- 71 SoftTex Dune softly etched reflector. (CP x .95)
- 72 Black specular Alzak reflector. (CP x .87)
- 77 SoftTex Pewter softly etched reflector. (CP x .90)
- 90 SoftTex Champagne Gold softly etched reflector. (CP x .96)
- 91 SoftTex Wheat softly etched reflector. (CP x .95)
- 92 Umber specular Alzak reflector. (CP x .92)
- 93 Pewter specular Alzak reflector. (CP x .95)
- 94 Custom color reflector. Consult factory.
- OG OptiGroove black seamless tapered aluminum reflector. White trim. (CP x .90)

Lenses and Trims

(HPR-06211, HPR-06212 only)

- 27 Clear 1/4" tempered glass beneath prismatic C#73 flat glass lens for impact resistance.
- 40 White grooveless flare trim assembly instead.
- 45 Gasket between trim and housing.
- 46 Gasket between trim and lens.

- 94 Custom color trim assembly. Consult factory.
- FR Fresnel tempered lens instead.

Luminaire (Housing) Finishes

- 35 Natural Aluminum enameled luminaire finish instead.
- 36 Gold enameled luminaire finish instead.
- 37 Dark Bronze enameled luminaire finish instead.
- 38 Black enameled luminaire finish instead.
- 94 Custom color luminaire finish. Consult factory.

Mounting Options

- 54 Safety cable through pendant stem. 12" longer than specified stem length. Anchored to fixture. Use with Option -PM.
- 87 Custom -PM length. Specify up to 4 feet or consult factory for longer lengths with couplers.
- 88 Swivel canopy for sloped ceilings up to 45°.
- 89 Earthquake rated. Use with Option -PM.
- 89 Sealed top feature prevents moisture and insect intrusion from above in outdoor or high humidity areas. Must use with pendant mount or Option -WB for Wet Label listing.
- WB Wall bracket mount instead. Also see Option -89.

Other Options

- 99 Special modification. Consult factory.

KIRLIN

THE KIRLIN COMPANY

3401 EAST JEFFERSON AVENUE • DETROIT, MICHIGAN 48207-4232
(313) 259-6400 • Fax: (313) 259-3121 or (313) 259-9409 • www.kirlinlighting.com

THE KIRLIN COMPANY RESERVES THE RIGHT TO CHANGE, WITHOUT NOTICE, DETAILS OR SPECIFICATIONS IN PRODUCT DESIGN.

Alzak® is a registered trademark of ALCOA.

