

Recessed Round PAR Lamp
Open Adjustable
39 to 150 Watt

THIS PRODUCT IS NO LONGER AVAILABLE

4" 70W
6" 150W
7" 150W

HRR-04007
HRR-06008
HRR-07009

Features

Lamp

- Designed for metal halide PAR lamps. See chart below for standard and optional lamp wattages.
- See Option -43 and chart below for lower wattage.

Socket Assembly - Open Adjustables

- Swivels 38° and tilts up to 45°.

Socket

- Medium base. Pulse rated. Glaze performance.
- Nickel-plated brass screw shell. Silicone leads.

Reflector

- Self-flanged clear specular Alzak® aluminum optional reflector finish available.
- Thirteen optional reflector finishes available.

Ballast Assembly: Specify Voltage

- Whisper™ fully encapsulated 180°C rated HP ballast.

- Premium Class H: High reactance for 120 volt, line reactor for 277 volt.
- Capacitor and inductor start.
- Dimming (-39) and electronic (-43) ballasts available. See Options.

- Cool, quiet, long-life. Silicone leads.
- Visible and easily serviced in all ceilings including dry wall.

Fuse

- Fused primary. Renewable. Not for 480 volt.
- Style: Enamelled aluminum.
- Cool: Dissipates heat across entire surface.

- Must protect ceiling 120 hours.

- Entire luminaire serviced through removable reflector. For top access see Option -TA.

Outlet Box

- Prewired 14 GA (NEC) galvanized steel, UL listed; with removable insulated cover.
- 1/2" and 3/4" knockouts.

Installation

- 27" galvanized hanger bars supplied (2).
- Fully adjustable universal mounting brackets supplied (2).
- Recesses indoor or outdoor in covered locations.

UL, C-UL (Canada) Listings

- Wet, damp or dry locations, covered ceilings.
- Through-branch circuit conductors (6 #12).

Three Year Limited Warranty

- Complete standard fixture, including ballast.

Thermal Protection

- UL listed.

Please consult
QUOTATIONS
for the best alternative.

Wattage / Lamp Availability and Cut-Out Dimensions

Catalog No.	Designed For:			Option -43: Lower Wattage	Ceiling Cut-Out Diameter	Fixture Style
	Standard	Lamp	Optional Lamp(s)			
HRR-04007	70 PAR 30	10° SP	40° MFL	39	5.0"	Open Adjustable
HRR-06008	150 PAR 38	20° SP	35° MFL 65° FL	70-100	6.5"	Open Adjustable
HRR-07009	150 PAR 38	20° SP	35° MFL 65° FL	70-100	8.0"	Open Adjustable

Options

Sources and Ballasts

- 39 Electronic dimming ballast instead, for pulse start metal halide. Consult factory for wattage and voltage availability.
- 96 Regulating electronic MH ballast instead.

Wattage and Voltage

- 43 Lower wattage. See Option -43 chart above for available lower wattages. Specify voltage.
- 120 120 volt, 60 Hz. ballast.
- 277 277 volt, 60 Hz. ballast.
- 347 347 volt, 60 Hz. ballast. Consult factory for dimming or electronic.
- 97 Other voltage ballast instead. Consult factory.

Lamps (See Chart)

- LP With lamp. Choose standard lamp shown above or specify wattage, beam spread, style (PAR 20, PAR 30, PAR 38), brand and color temperature.

Reflectors and Trims (Self-Flanged)

- 16 Champagne Gold specular Alzak reflector. (CP x .98)
- 30 All White reflector. (CP x .98)
- 31 White flange (only) on self-flanged reflector.
- 32 Trim extender. Broadens trim flange O.D. by 1" to cover larger ceiling opening.
- 45 Gasket above reflector flange. Stops dust streaks on ceiling.
- 63 Dune specular Alzak reflector. (CP x .97)
- 69 Wheat specular Alzak reflector. (CP x .97)
- 70 SoFTex Clear softly etched reflector. Resists smudges. (CP x .98)
- 71 SoFTex Dune softly etched reflector. Resists smudges. (CP x .95)
- 72 Black specular Alzak reflector. (CP x .87)
- 77 SoFTex Pewter softly etched reflector. Resists smudges. (CP x .90)

- 90 SoFTex Champagne Gold softly etched reflector. Resists smudges. (CP x .96)
- 91 SoFTex Wheat softly etched reflector. Resists smudges. (CP x .95)
- 92 Umber specular Alzak reflector. (CP x .92)
- 93 Pewter specular Alzak reflector. (CP x .95)
- 94 Custom color reflector. Consult factory.

Other Options

- 99 Special modification. Consult factory.
- TA Top access modification for servicing from above ceiling.

KIRLIN

THE KIRLIN COMPANY

3401 EAST JEFFERSON AVENUE • DETROIT, MICHIGAN 48207-4232
(313) 259-6400 • Fax: (313) 259-9409 or (313) 259-3121 • www.kirlinlighting.com

THE KIRLIN COMPANY RESERVES THE RIGHT TO CHANGE, WITHOUT NOTICE, DETAILS OR SPECIFICATIONS IN PRODUCT DESIGN.

Alzak® is a registered trademark of ALCOA.

