

CATALOG #	TYPE	
JOB NAME	WATTAGE	VOLTAGE

## Wayfinding Series

### Lensed Steplight 3" x 7" Steplight • LED

Super Shallow • Type IC • Optional LED Filter Colors

## Specifications

#### LED

- White module (colored filters optional)
- 3500°K standard
- 5.5 system watts - energy efficient, uniform, cool

#### LED Power Supply/Driver

- Max 13 volt DC and 4 watt fixed output; electronically stabilized
- Minimum operating temperature -4°F (-20°C)
- 120-277 volt standard; load insensitive

#### Lens

- Translucent white 1/8" polycarbonate sealed to trim

#### Faceplate

- Gasketed aluminum frame pulls tight to wall

- White finish standard; optional colors
- Optional (white only) antimicrobial Kirlin BioGard™ finish; see Option-BG
- Tamper resistant available; see Options
- Removable for servicing

#### Housing: Shallow 2½" Depth

- Cool; acrylic enameled aluminum
- Rustproof: Exceeds 1000 hour ASTM 5% salt spray test
- Dissipates heat across entire surface area

#### Installation

- Recesses indoor or outdoor, covered locations
- Mounting holes on housing ends

## LNT-03096



#### UL, C-UL (Canada) Listings

- Damp or dry locations
- Type IC; approved for direct contact with insulation

#### FIVE YEAR Limited Warranty

- Complete standard fixture





## Options and Ordering Configuration

(Example: LNT-03096-BL-37-26)

Required	Optional			
Model	Voltage/Battery Pack	Filter Colors	Faceplate Finishes	Other Options
LNT-03096				
	<b>(Blank):</b> Universal 120-277 V  <b>-97:</b> Other voltage input; consult factory  <b>-EI:</b> Remote emergency inverter for 100% of rated lumens; Run time: 90+ minutes; 120 or 277V, 60Hz input only; specify voltage	<b>(Blank):</b> None  <b>-BL:</b> Blue filter <b>-GE:</b> Green filter <b>-OR:</b> Orange filter <b>-RA:</b> Red/Amber filter <b>-YE:</b> Yellow filter <b>-CF:</b> Custom color filter (Rosco); specify	<b>(Blank):</b> Standard white finish  <b>-35:</b> Silver (natural aluminum) acrylic enamel <b>-37:</b> Dark bronze acrylic enamel <b>-38:</b> Black acrylic enamel <b>-94:</b> Custom color; consult factory <b>-BG:</b> BioGard™ anti-microbial white	<b>(Blank):</b> None  <b>-26:</b> Faceplate secured to housing with two center pin tamperproof screws; tamperproof tool included  <b>-99:</b> Special modification; consult factory

## Dimensions




## LED Filter Colors




Photometry - Installed Complete Fixture

LM-79 IESNA Certified Photometry from Independent Lab



Footcandle Performance On the Floor - Top View  
ITL Test: 89230



LIMITED WARRANTY: KIRLIN LIGHTING FIXTURES ARE WARRANTED FREE OF DEFECTS IN WORKMANSHIP OR MATERIAL FOR FIVE YEARS FROM DATE OF PURCHASE. INSTALLATION, IN NORMAL USE, MANUFACTURER'S WARRANTY WILL REPLACE OR REPAIR SUCH FIXTURE OR REFUND THE PURCHASE PRICE ON PRESENTATION OF PROOF OF PURCHASE AND DEFECTIVE FIXTURE AT THE OFFICE OF MANUFACTURER WITHIN TWO YEARS OF ORIGINAL SHIPMENT. LIABILITY OF MANUFACTURER IS LIMITED TO THE FOREGOING AND MANUFACTURER SHALL NOT BE LIABLE FOR ANY OTHER DAMAGES, DIRECT OR INDIRECT, SUSTAINED OR SUFFERED BY PURCHASER OR ANY PERSON. THIS WARRANTY IS SUPPLIED TO THE BUYER IN PLACE OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. SELLER DOES NOT WARRANT AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE, NOR WILL ANY ORAL STATEMENT CONSTITUTE A WARRANTY, ABNORMAL USE, ABUSE OF THE FIXTURE, IMPROPER INSTALLATION, OR REPAIR, OR MODIFICATION OF THE FIXTURE WITHOUT PRIOR WRITTEN AUTHORIZATION FROM THE MANUFACTURER WILL RENDER THE WARRANTY VOID.