

CATALOG#		TYPE	
JOB NAME	WATTAGE	VOLTAGE	

Wayfinding Series

"Brick Light" 3" x 8" Nightlight • LED

50,000 Hour Rated Life • Type IC • Optional LED Filter Colors

Specifications

LEC

- · White module (colored filters optional)
- · 3500°K standard
- 5.5 system watts energy efficient, uniform, cool

LED Power Supply/Driver

- Max 13 volt DC and 4 watt fixed output; electronically stabilized
- Minimum operating temperature -4°F (-20°C)
- 120-277 volt standard; load insensitive

Lens

· Clear poly lenses behind louver

Faceplate

- Seamless die-formed gasketed louvered door pulls tight to wall
- · White finish standard; optional colors

- Optional (white only) antimicrobial Kirlin BioGard™ finish; see Option -BG
- · Tamper resistant available; see Options
- · Removable for servicing

Housing: Shallow 21/2" Depth

- Cool; acrylic enameled aluminum
- Rustproof: Exceeds 1000 hour ASTM 5% salt spray test
- · Dissipates heat across entire surface area

Installation

- Recesses in wall indoor or outdoor, covered locations
- Mounting holes on housing ends
- Adjustable mounting brackets allow installation between adjoining studs up to 22" apart

LNT-03098



UL, C-UL (Canada) Listings

- · Damp or dry locations
- · See Option -WL for wet locations
- Type IC; approved for direct contact with insulation

FIVE YEAR Limited Warranty

· Complete standard fixture











Options and Ordering Configuration (Example: LNT-03098-BL-37-26)

Required	Optional				
Model	Voltage/Battery Pack	Filter Colors	Louvered Door Finishes	Other Options	
LNT-03098					
	(Blank): Universal 120-277 V	(Blank): None	(Blank): Standard white finish	(Blank): None	
	-97: Other voltage input; consult factory -EI: Remote emergency inverter for 100% of rated lumens; Run time: 90+ minutes; 120 or 277V, 60Hz input only; specify voltage	-BL: Blue filter -GE: Green filter -OR: Orange filter -RA: Red/Amber filter -YE: Yellow filter -CF: Custom color filter (Rosco); specify	-35: Silver (natural aluminum) acrylic enamel -37: Dark bronze acrylic enamel -38: Black acrylic enamel -BG: BioGard™ anti-microbial white -BKBG: BioGard™ anti-microbial black -94: Custom color; consult factory -94BG: BioGard™ anti-microbial custom color finish	-26: Faceplate secured to housing with two center pin tamperproof screws; tamperproof tool included -99: Special modification; consult factory -WL: UL Wet Location listed; not available with switch or receptacle options	

Dimensions






LED Filter Colors





Photometry - Installed Complete Fixture

LM-79 IES Certified Photometry from Independent Lab



Footcandle Performance On the Floor - Top View ITL Test: 89228

