

CATALOG #	TYPE	
JOB NAME	WATTAGE	VOLTAGE

Lighting for Patient Spaces

2'x 2' Surface-Mounted White or Scenic Panel

Ligature & Vandal Resistant • Soothing & Safe “Skylight” Effect
Up to 60,000 Hour Life • 90 CRI

Specifications

Delivered System Performance

- Lumen Series: **MUST SPECIFY**
-2500L (35W) - Not available with images
-1500L (20W)
- Color temperature: **MUST SPECIFY**
3500°K or 4100°K
- Distribution: WFL
- 90 CRI; 60,000 hour life (L70)

Thermal Management System

- Heavy gauge aluminum construction provides maximum heat dissipation for cool LED operation; extends life of all components

LED Driver - INTERNAL

- Indoor/Outdoor: -30°C to 60°C (-22°F to 140°F)
- 0-10V 1.0% dimming standard
- Voltage: 120-277/50-60Hz; load insensitive
- Enclosed in aluminum housing

IK10 Trim/Lens - Ligature/Vandal Resistant

- Rigid tempered heavy gauge 6063-T5 aluminum housing and single-piece frame with seam welded corners and keys
- Rustproof and corrosion resistant
- BioGard™ antimicrobial white finish
- Flush center pin tamperproof screws: tamperproof tool included
- High strength clear flat polycarbonate (0.220") - environmental side
- Extruded acrylic wave guide provides unparalleled uniformity
- Lightweight: minimizes ceiling load

Scenic Panel Image (Optional)

- Acrylic scenic panel (Over 100 selections from Kirlin or customer-provided) above polycarbonate
- Easily changed without replacing luminaire for a cost-effective interior design update
- Visualize your design with Kirlin's [Scenic Configurator](#) tool

MSV-22866



Outlet Box (Galvanized)

- UL listed J-box; prewired 16 GA steel with ½" knockouts

Installation & Hardware

- Direct mount to any hard surface ceiling; mounting hardware by others
- Suitable for indoor use
- UL, C-UL (Canada) Listings**
- Wet, damp or dry locations, covered ceilings

FCC Compliance

- FCC Part 15 certified for EMI/RFI emissions

FIVE YEAR Limited Warranty

- Complete standard fixture

THIS FIXTURE HAS BEEN DISCONTINUED - CONTACT FACTORY FOR ALTERNATIVES



Vandal Resistant



IK10 Impact Resistant



Made in the USA
BABA Compliant



BioGard™





FCC Part 15
Certified



UL Listed
Wet, Damp, Dry

Dimensions





(Example: MSV-22866-1500L-41K-IMG)

Must Specify			Optional			
Model	Lumens	CCT & CRI	Image	Driver Options	Trim Finish	Other Options
MSV-22866						
	-2500L† -1500L † 2500L not available with images	(Blank): 35K, 90+ CRI -35K: 3500K -41K: 4000K	(Blank): White Panel -IMG: Scenic Panel; N/A with -2500L Choose the image desired from the Scenic Image Gallery brochure; Order the scenic image seperately	(Blank): 0-10V 1.0% dimming -D6: Triac 100-10% dimming instead	(Blank): White BioGard™ anti-microbial finish -BKBG: BioGard™ anti-microbial black -94: Custom color/finish; see page 4 for recommended custom colors; consult factory -94BG: BioGard™ anti-microbial custom color finish	(Blank): None -99: Special modification; consult factory

(Example: MRP-22IMG-2X2-SKY10)

Must Specify			Options
Model	Size	Image	Other Options
MRP-22IMG			
	-2X2: 1 panel	Choose the image desired from the Scenic Image Gallery brochure and insert the code here. To see how your artwork will appear in an arrangement, visit Kirlin's Scenic Configurator tool.	(Blank): None
		-IMG99: Custom image† † See requirements on page 5	-99: Special modification; consult factory
	See the next page for additional layout and orientation details.		If ordering a -PAT image, choose the pattern color desired from the Scenic Image Gallery brochure and insert the code here.

LM-79 IESNA Certified Photometry from Independent Lab



LED manufacturers maintain a tolerance of +/-7% on flux (lumens) and power (electrical) measurements.

Scenic Panel Options



Image Gallery

- Sky (SKY) - 25 Images
- Night Sky (NGT) - 7 Images
- Space (SPC) - 4 Images
- Tree (TRE) - 22 Images
- Nature Landscape (LND) - 8 Images
- Water (WTR) - 5 Images
- Abstract Art (ART) - 10 Images
- Patterns (PAT) - 25 Patterns

THIS FIXTURE HAS
BEEN DISCONTINUED. CONTACT
FACTORY FOR ALTERNATIVES.


LIMITED WARRANTY: KIRLIN EXTLITES ARE WARRANTED FREE OF DEFECTS IN WORKMANSHIP OR MATERIAL FOR FIVE YEARS FROM DATE OF PURCHASE. INSTALLATION, E.G., IN NORMAL USE. Manufacturer at his option will replace or repair such fixture or refund the purchase price on presentation of proof of purchase and defective fixture at the offices of manufacturer within five years of original shipment. Liability of manufacturer is limited to the foregoing and manufacturer shall not be liable for any other damages, direct or indirect, sustained or suffered by purchaser or any person. This warranty is supplied to the buyer in place of all other warranties, expressed or implied. Seller does not warrant as to merchantability or fitness for a particular use, nor will any oral statement constitute a warranty or amend this specific warranty. Abnormal use, abuse of the fixture, improper installation, or repair or modification of the fixture without prior written authorization from the manufacturer will render the warranty void.

PATENT SPACES
DECEMBER 2024


Recommended Custom Colors

The below colors match Kirlin's Scenic Patterns for a cohesive look throughout the space.
To be used with option code -94.

Calming Colors




Pale Marigold




Peaceful Pine



Moonlit Bay



Dreamy Dusk



Mudstone Magic




Soft Slate


Vibrant Colors




Electric Ember



Hot Orchid



Lemon Zing




Kiwi Kick



Caribbean Lagoon



Cerulean Wave



Glam Grape

Due to variations in monitor settings and screen resolutions, the appearance of colors, textures, and details in the images may differ from the actual product.