

CATALOG #	TYPE	
JOB NAME	WATTAGE	VOLTAGE

Gazelle Series

6" Regressed Lens Downlight • LED

Type IC • LM-79 Certified • LM-80 Qualified



QuickShip
Program
Luminaire

GRR-06219



Specifications

Delivered System Performance

- Nominal Lumens: **Must Specify**

Type IC

-2000L

-1500L

-1000L

- Select trim & beam distribution: see chart
- Select color (CCT): see chart; 80+ CRI standard
- 90,000 hour life (L70**)

Thermal Management System

- Aluminum heat sink and components for cool operation, long life, and low maintenance

LED Driver - INTERNAL

- Indoor/Outdoor: -30°C to 60°C (-22°F to 140°F)
- 0-10V CCR 10% dimming standard
- 120-277V / 50-60 Hz standard; load insensitive

Trim

- White aluminum self-flanged downlight (field paintable)
- Regressed tempered prismatic spread lens

Acrylic Enamelled Aluminum Housing

- Rustproof and corrosion resistant: exceeds 1000 hour ASTM 5% salt spray test
- Shallow depth fits restricted plenums
- Cool operation extends component life
- Modular design; visible and fully serviceable through aperture
- Built-in plaster flange

Outlet Box (Galvanized)

- UL Listed; 14GA, insulated, removable cover
- 1/2" and 3/4" knockouts

Installation & Hardware

- Indoor/outdoor in ceilings up to 1 1/8" thick
- Compatible with fire rated enclosures (by others)
- 27" hanger bars & adjusting brackets (2) supplied

UL, C-UL (Canada) Compliance

- Wet, damp or dry locations, covered ceilings
- Type IC for direct contact with insulation
- Through-branch conductors (4 #12 AWG 90°C) for Type IC Listing

IEC & FCC Compliance

- Meets IEC/EN 60601-1-2 electromagnetic compatibility standard for medical electrical equipment
- FCC Part 15 certified for EMI/RFI emissions

FIVE YEAR Limited Warranty

- Complete standard fixture

Made in the USA
BAA Compliant

FCC Part 15
Certified

UL Listed
Wet, Damp, Dry

Options and Ordering Configuration

(Example: GRR-06219-1500L-277-WFL-30K-EI-46)

Must Specify												
Model	Lumens	Volts	Beam	CCT & CRI	Emergency Options	Trim Options						
GRR-06219	-2000L -1500L -1000L	(Blank): 120-277 -120 -277	(Blank): WFL -SPT -NFL -MFL -WFL	(Blank): 3500°K, 80+ CRI -30K: 3000°K -35K: 3500°K -41K: 4100°K	(Blank): None -EI: Remote emergency inverter for 100% rated lumens; Run time: 90+ minutes. 120 or 277V, 60 Hz input only. Specify voltage.	(Blank): Standard white aluminum -45: Gasket between trim & ceiling -46: Gasket between trim & lens						
<div style="display: flex; justify-content: space-between; align-items: center;"> <div style="text-align: right;"> <p>QuickShip Program Luminaire</p> <ul style="list-style-type: none"> Orders received by 10 AM (ET) ship by 5 PM within 5 business days Freight allowed: Over \$8000 Consult factory for quantities greater than 200 units </div> </div>												
<table border="1" style="margin: auto;"> <tr> <th colspan="2">Projected L70** for Kirlin Luminaires</th> </tr> <tr> <td>In Open Plenum</td> <td>90,000 hours</td> </tr> <tr> <td>In Insulation (Type IC)</td> <td>60,000 hours</td> </tr> </table> <p>**Hours at 70% lumen maintenance</p>							Projected L70** for Kirlin Luminaires		In Open Plenum	90,000 hours	In Insulation (Type IC)	60,000 hours
Projected L70** for Kirlin Luminaires												
In Open Plenum	90,000 hours											
In Insulation (Type IC)	60,000 hours											

